



Default Settings for JET-TECH MAX

Copyright © 2007 Jet-Tech Motorsport

No publication in full or in part of this document may be made without the express written permission of the author.

These are the default or 'Factory' settings for Jet-Tech MAX. You can use these settings as a starting point for each configuration. They represent the standard settings for each engine/carb combination to match the configuration that the engine/carb comes with from Rotax. As such, they are likely to be on the 'rich but safe' side. To use them, select the button that you want to save the settings in ("DD2", "Snr", "Jnr", "Mini" or "Micro"). If you run more than one engine/carb, you can save each setup to one of the other buttons.

Firstly, set your barometer readings to the following:

Temperature = 15°C / 59°F

Humidity = 0%

Pressure = 1013mb / 29.91Hg

Then enter the default settings. When this is completed, you can then start to change the settings to mirror your own configuration. For example, changing the needle, float weights and height etc. You can then put in your actual barometer readings and start the fine-tuning process.

For further information on setting up your software to perfectly match your unique engine/carb combinations, please see the 'Help' file by pressing 'F1' or the '?' in the corner of the Jet-Tech screen. You can also view the tutorial videos at http://www.rotaxjetting.com/video_tutorials.htm

ROTAX FR125 DD2

Needle	K27
Floats	5.2g
Idle Jet	30
Float Height	6mm
Needle Design Factor	493
Main Jet Factor	643

ROTAX FR125 MAX SENIOR

Needle	K27
Floats	5.2g
Idle Jet	30
Float Height	6mm
Needle Design Factor	492
Main Jet Factor	480

ROTAX FR125 MAX JUNIOR

Needle	K27
Floats	5.2g
Idle Jet	30
Float Height	6mm
Needle Design Factor	493
Main Jet Factor	467

ROTAX FR125 MAX MINI

Needle	K98
Floats	3.6g
Idle Jet	60
Float Height	6mm
Needle Design Factor	460
Main Jet Factor	378

ROTAX FR125 MAX MICRO

Needle	K98
Floats	3.6g
Idle Jet	60
Float Height	6mm
Needle Design Factor	460
Main Jet Factor	256

